

**GR COOLING UNIT**

		<b>GR 02</b>	<b>GR 07</b>	<b>GR 12</b>	<b>GR 12T</b>	<b>GR 20</b>	<b>GR 20T</b>	<b>GR 45T</b>
<b>Power Supply</b>	V-Hz	230-1-50	230-1-50	230-1-50	400-3-50	230-1-50	400-3-50	400-3-5
<b>Cooling current*</b>	kW	0.2	0.7	1.2	1.2	2	2	4.6
	kcal/h	170	600	1030	1030	1720	1720	3960
<b>Total input power</b>	kW	0.49	0.79	1.05	0.95	1.55	1.45	2.9
<b>Water flow</b>	l/min	1-12	10-60	3-50	3-50	3-50	3-50	3-50
<b>Pressure range</b>	bar	3.5-0.5	1.5-0.7	2.6-1.6	2.6-1.6	2.6-1.6	2.6-1.6	2.2-1.6
<b>Water tank volume</b>	l	5	8	8	8	30	30	30
<b>Air flow</b>	m <sup>3</sup> /h	255	390	570	570	900	900	2000
<b>Dimensions</b>	A mm	260	310	360	360	450	450	1050
	B mm	410	460	560	560	660	660	626
<b>Weight empty</b>	C mm	410	620	660	660	760	760	627
	KG	26	40	50	65	72	85	135

\* For 10°C outlet water, 32°C ambient.